

# SAFETY DATA SHEET

Creation Date 26-Mar-2014

Revision Date 26-Mar-2014

Revision Number 1

## 1. Identification

**Product Name** Cytoseal™ 60

**Cat No. :** 8310-4, 8310-16, V8310-4

**Synonyms** No information available.

**Recommended Use** Laboratory chemicals

**Uses advised against** No Information available

### Details of the supplier of the safety data sheet

<b>Company</b>	<b>Emergency Telephone Number</b>
Richard Allan Scientific	Chemtrec US: (800) 424-9300
A Subsidiary of Thermo Fisher Scientific	Chemtrec EU: 001 (202) 483-7616
4481 Campus Drive	
Kalamazoo, MI 49008	
Tel: (800) 522-7270	

## 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Skin Corrosion/irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Liver, Heart, Blood.	
Aspiration Toxicity	Category 1

### Label Elements

#### **Signal Word**

Danger

#### **Hazard Statements**

Highly flammable liquid and vapor  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness  
May damage fertility or the unborn child  
Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection  
Do not breathe dust/fume/gas/mist/vapors/spray  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

**Response**

IF exposed or concerned: Get medical attention/advice

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Skin**

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention.

**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

**Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Harmful to aquatic life with long lasting effects

### 3. Composition / information on ingredients

### 3. Composition / information on ingredients

**Haz/Non-haz**

Component	CAS-No	Weight %
Toluene	108-88-3	70-73
Acrylic Resin	28262-63-7	25 - 28
Butyl benzyl phthalate	85-68-7	<1
2,6-Di-tert-butyl-p-cresol	128-37-0	< 1.0

### 4. First-aid measures

**General Advice**

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

**Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin Contact**

Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention. Call a physician immediately. **SPEEDY ACTION IS CRITICAL, GET MEDICAL AID IMMEDIATELY..** If symptoms persist, call a physician. If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

**Inhalation**

Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a respiratory medical device. Immediate medical attention is required. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.

**Ingestion**

Do not induce vomiting. Call a physician or Poison Control Center immediately. Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.

**Most important symptoms/effects**

Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Notes to Physician**

Treat symptomatically.

### 5. Fire-fighting measures

**Suitable Extinguishing Media**

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Use water spray to cool unopened containers.

**Unsuitable Extinguishing Media**

Water may be ineffective

**Flash Point**

4.44°C / 40°F

**Method -**

No information available

**Autoignition Temperature**

No information available.

**Explosion Limits****Upper**

No data available

**Lower**

No data available

**Sensitivity to Mechanical**

No information available

**Impact**

**Sensitivity to Static Discharge** No information available

**Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

**Hazardous Combustion Products** Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

**NFPA**

**Health**  
3

**Flammability**  
3

**Instability**  
0

**Physical hazards**  
N/A

## 6. Accidental release measures

**Personal Precautions**

Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Environmental Precautions**

Should not be released into the environment. See Section 12 for additional ecological Information. Avoid release to the environment. Collect spillage. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

**Methods for Containment and Clean Up**

Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal.

## 7. Handling and storage

**Handling**

Use only under a chemical fume hood. Wear personal protective equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Pay attention to flashback. No information available.. Do not take internally.

**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers.

## 8. Exposure controls / personal protection

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 375 mg/m <sup>3</sup> Ceiling: 300 ppm (Vacated) STEL: 150 ppm (Vacated) STEL: 560 mg/m <sup>3</sup> TWA: 200 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
2,6-Di-tert-butyl-p-cresol	TWA: 2 mg/m <sup>3</sup>	(Vacated) TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Toluene	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> Skin	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup>	TWA: 20 ppm

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
2,6-Di-tert-butyl-p-cresol	STEL: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>

**Legend****ACGIH** - American Conference of Governmental Hygienists**OSHA** - Occupational Safety and Health Administration**NIOSH IDLH**: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health**Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

**Personal Protective Equipment****Eye/face Protection**

Tightly fitting safety goggles. Face-shield.

**Skin and body protection**

Long sleeved clothing. Apron. Impervious gloves.

**Respiratory Protection**

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Hygiene Measures**

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

## 9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	aromatic
Odor Threshold	No information available.
pH	No information available.
Melting Point/Range	No data available
Boiling Point/Range	110.6°C / 231°F
Flash Point	4.44°C / 40°F
Evaporation Rate	No information available.
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	47 mmHg @ 20 °C
Vapor Density	No information available.
Relative Density	0.97
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available.
Decomposition temperature	No information available.
Viscosity	No information available.

## 10. Stability and reactivity

**Reactive Hazard**

None known, based on information available.

**Stability**

Stable under normal conditions.

**Conditions to Avoid**

Incompatible products. Heat, flames and sparks.

<b>Incompatible Materials</b>	Strong oxidizing agents, Strong acids
<b>Hazardous Decomposition Products</b>	Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> )
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing

## 11. Toxicological information

### Acute Toxicity

<b>Product Information</b>	No acute toxicity information is available for this product
<b>Oral LD50</b>	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
<b>Dermal LD50</b>	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
<b>Vapor LC50</b>	Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg ( Rat )	8390 mg/kg ( Rabbit )	26700 ppm ( Rat ) 1 h
Butyl benzyl phthalate	2330 mg/kg ( Rat )	6700 mg/kg ( Rat )	6.7 mg/L ( Rat ) 4 h
2,6-Di-tert-butyl-p-cresol	890 mg/kg ( Rat ) >2000 mg/kg ( Rat )	Not listed	Not listed

<b>Toxicologically Synergistic Products</b>	No information available.
---	---------------------------

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Irritation</b>	Irritating to eyes and skin
<b>Sensitization</b>	No information available.
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Toluene	108-88-3	Not listed	Not listed	Not listed	Not listed	Not listed
Acrylic Resin	28262-63-7	Not listed	Not listed	Not listed	Not listed	Not listed
Butyl benzyl phthalate	85-68-7	group 3	Not listed	Not listed	Not listed	Not listed
2,6-Di-tert-butyl-p-cresol	128-37-0	Not listed	Not listed	Not listed	Not listed	Not listed

**IARC: (International Agency for Research on Cancer)**

**IARC: (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

<b>Mutagenic Effects</b>	Mutagenic effects have occurred in humans.
<b>Reproductive Effects</b>	Experiments have shown reproductive toxicity effects on laboratory animals.
<b>Developmental Effects</b>	Developmental effects have occurred in experimental animals.
<b>Teratogenicity</b>	Teratogenic effects have occurred in experimental animals..
<b>STOT - single exposure</b>	Central nervous system (CNS).
<b>STOT - repeated exposure</b>	Kidney, Liver, Heart, Blood.
<b>Aspiration hazard</b>	No information available.

**Symptoms / effects,  
both acute and delayed**

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Endocrine Disruptor Information**

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Butyl benzyl phthalate	Group I Chemical	High Exposure Concern	Not applicable

**Other Adverse Effects**

See actual entry in RTECS for complete information.

## 12. Ecological information

**Ecotoxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Toluene	433 mg/L EC50 > 96 h 12.5 mg/L EC50 = 72 h	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	11.5 mg/L EC50 = 48 h 5.46 - 9.83 mg/L EC50 48 h
Butyl benzyl phthalate	0.2 - 28.2 mg/L EC50 72 h 0.02 - 0.25 mg/L EC50 96 h	Lepomis macrochirus: LC50=1.7 mg/L 96h Salmo gairdneri: LC50=1.1 mg/L 96h	Not listed	0.97 mg/L EC50 = 48 h 1.28 mg/L EC50 = 48 h 0.76 mg/L EC50 > 48 h 0.9 - 1.1 mg/L EC50 48 h
2,6-Di-tert-butyl-p-cresol	EC50 = 0.758 mg/L 96h EC50 = 6 mg/L 72 h	LC50 = 0.199 mg/L 96h	EC50 = 7.82 mg/L 5 min EC50 = 8.57 mg/L 15 min EC50 = 8.98 mg/L 30 min	EC50 > 0.31 mg/L 48h

**Persistence and Degradability**

No information available.

**Bioaccumulation/ Accumulation**

No information available

**Mobility**

Component	log Pow
Toluene	2.65
Butyl benzyl phthalate	4.91
2,6-Di-tert-butyl-p-cresol	4.17

## 13. Disposal considerations

**Waste Disposal Methods**

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Toluene - 108-88-3	U220	-

## 14. Transport information

**DOT**

UN-No	UN1866
Proper Shipping Name	RESIN SOLUTION
Hazard Class	3

## 14. Transport information

Packing Group II

### TDG

UN-No UN1866  
 Proper Shipping Name RESIN SOLUTION  
 Hazard Class 3  
 Packing Group II

### IATA

UN-No UN1866  
 Proper Shipping Name RESIN SOLUTION  
 Hazard Class 3  
 Packing Group II

### IMDG/IMO

UN-No UN1866  
 Proper Shipping Name RESIN SOLUTION  
 Hazard Class 3  
 Packing Group II

## 15. Regulatory information

### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Toluene	X	X	-	203-625-9	-		X	X	X	X	X
Acrylic Resin	X	X	-	-	-		X	X	X	X	X
Butyl benzyl phthalate	X	X	-	201-622-7	-		X	X	X	X	X
2,6-Di-tert-butyl-p-cresol	X	X	-	204-881-4	-		X	X	X	X	X

### Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### U.S. Federal Regulations

#### TSCA 12(b)

Not applicable

#### SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	70-73	1.0



**SARA 311/312 Hazardous Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Toluene	X	1000 lb	X	X
Butyl benzyl phthalate	-	-	X	X

**Clean Air Act**

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene	X		-

OSHA Occupational Safety and Health Administration

OSHA - Occupational Safety and Health Administration

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Toluene	1000 lb	-
Butyl benzyl phthalate	100 lb	-

**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65	Prop 65 NSRL
Toluene	108-88-3	Developmental Female Reproductive	-
Butyl benzyl phthalate	85-68-7	Developmental	-

**State Right-to-Know**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Toluene	X	X	X	X	X
Butyl benzyl phthalate	X	X	X	X	-
2,6-Di-tert-butyl-p-cresol	X	X	X	-	X

**U.S. Department of Transportation**

Reportable Quantity (RQ):	Y
DOT Marine Pollutant	N
DOT Severe Marine Pollutant	N

**U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

**Other International Regulations**

**Mexico - Grade** Serious risk, Grade 3

**Canada**

—

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class                      B2 Flammable liquid  
D2A Very toxic materials



## 16. Other information

Prepared By	Regulatory Affairs Richard Allan Scientific A Subsidiary of Thermo Fisher Scientific Tel: (800) 522-7270
Creation Date	26-Mar-2014
Revision Date	26-Mar-2014
Print Date	26-Mar-2014
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**